

3M™ All Weather Flashing Tape 8067

Sticks
fast
at 0-120°F

Stays stuck
at up to 176°F



No primers, no staples, no nonsense

With unique pressure sensitive acrylic adhesive, 3M™ All Weather Flashing Tape 8067 bonds on contact to seal through-wall penetrations at application temperatures from 0°F (-18°C) up to 120°F (49°C). Around windows, doors and other openings in wood frame construction, you save the time and work of primers or staples commonly used to attach many moisture-proofing membranes.

Engineered for handling ease and performance reliability

- High tack to grab fast and tight even on damp surfaces
 - Versatile to stick securely to most common building materials even at service temperature up to 176°F (80°C)
 - Proprietary backing for long term confidence
 - Seals around nails and staples to prevent moisture intrusion
 - Thin for a reliable and convenient fit into corners and under siding
 - Tough to resist punctures and tears during application and service life
- Fast, convenient application
 - No adhesive melting or staining in the summer's heat
 - Split-liner for easy and accurate positioning of tape, especially long lengths
 - Choice of three widths for the coverage you need: 4", 6", 9"
 - Resists UV exposure for up to 6 months
 - No adverse reaction with many building sealants (preliminary data for synthetic rubber, butyl, polyurethane, silicone and silane terminated hybrids).
 - Meets AAMA 711-05
 - Passes Nail Sealability before and after Thermal Cycling
 - Eligible for LEED® Compliance Credits



Authorized Distributor
Industrial Products



North American Distributor
of Industrial Supplies

Order Online, 24 hours a day, NO MINIMUM ORDER.

www.rshughes.com • 1-877-RSHUGHES • 1-877-774-8443